



Hints and features:

- Modern implement tyre for trailers and other farm machines with various uses, on grassland in particular
- Plant- and soil-protecting tread pattern
- Large contact area for low ground pressure and machine stability (on implements)
- Non-directional tread pattern with low rolling resistance and good self-cleaning properties

RAD 560 / 60 - 22.5 ALLIANCE FARMPRO 327
16 PR, 169 A8, TL, 10/281/335, A3, ET 0
16.00 X 22.5, RAL9006 SILBER, VS H

Product-No.: 59915910

Technical Information:

Wheel size	560 / 60 - 22.5
LI / PR	157 A8 / 169 A8, 16 PR
Tread	FarmPRO 327
Manufacturer	Alliance
Rim	AG 16.00 x 22.5 H2
Connection	10/281/335
Bolt hole execution	A3
Rim centering	BZ
Width [mm]	565
Outer diameter [mm]	1250
Static radius [mm]	547
Rolling circumference [mm]	3618
Inflation pressure [bar]	3,75
Loadcapacity Tyre	4125 / 40
Loadcapacity Rim	7600 / 40
Loadcapacity compl. Wheel	5800 / 40
Tread depth [mm]	21,0
Rim meterial	Stahl
RAL / Color	RAL9006 / Silber
Weight [Kg]	133,53