



REIFEN 500 / 60 R 22.5
155 D / 152 E, TL, RIDEMAX FL 693 M
STEEL BELTED, ECE106

Product-No.: 15715121

Technical Information:

Tyre size	500 / 60 R 22.5
TL / TT	TL
LI / SI	155 D / 152 E
Tread	Ridemax FL 693 M
Manufacturer	BKT
Specification	Steel Belted
Recom. Rim	AG16.00
Permissible rim	15, 17
Width [mm]	503
Outer diameter [mm]	1172
Static radius [mm]	531
Rolling circumference [mm]	3577
Payload in kg at kph (1)	3875 / 65
Payload in kg at kph (2)	3550 / 70
Inflation pressure [bar]	4,00
Weight [Kg]	100,31
Tyre content 75% [litre]	297
Stud height [mm]	21,0
Zulassung	ECE 106
Direction bound	Yes

Hints and features:

- Steel belted flotation tyre for versatile applications on a wide range of agricultural vehicles and trailers
- Enormous load capacity and high transport performance due to 65 km/h approval (in some cases even 70 km/h)
- Modern, directional tread pattern for very good road characteristics as well as cleaning properties when used in fields
- Low rolling resistance allows fuel savings

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.