





Hints and features:

- Municipal tyres for varied use, e.g. for tractors in contracting services with high road use or for green fodder and corn harvesting.
- Optimal winter performance due to special block tread pattern
- Low rolling resistance ensures high fuel savings compared with standard agricultural tyres
- Steel belt reinforcement for high load capacity and protection against punctures
- With M+S identification

REIFEN 360 / 70 R 20 129 A8 / 124 D, TL, MULTIUSE 550, M+S STEEL BELTED, BLOCK PROFIL, ECE106

Product-No.: 15284043

Technical Information:

Tyre size	360 / 70 R 20
TL/TT	TL
LI/SI	129 A8 / 124 D
Tread	Multiuse 550
Manufacturer	Alliance
Specification	M+S, Steel Belted
Recom. Rim	11
Permissible rim	10, 12
Width [mm]	355
Outer diameter [mm]	1051
Static radius [mm]	472
Rolling circumference [mm]	3121
Payload in kg at kph (1)	1850 / 40
Payload in kg at kph (2)	1600 / 65
Inflation pressure [bar]	2,40
Weight [Kg]	54,53
Tyre content 75% [litre]	120
Stud height [mm]	24,9
Zulassung	ECE 106
M+S	M+S

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.