

Firestone



REIFEN 300 / 95 R 46
162 A2 / 148 D, TL, PERFORMER 95

Product-No.: 10627332

Technical Information:

Tyre size	300 / 95 R 46
TL / TT	TL
LI / SI	162 A2 / 148 D
Tread	Performer 95
Manufacturer	Firestone
Recom. Rim	10
Permissible rim	9, 11
Width [mm]	313
Outer diameter [mm]	1737
Static radius [mm]	822
Rolling circumference [mm]	5348
Payload in kg at kph (1)	4750 / 10
Payload in kg at kph (2)	3150 / 65
Inflation pressure [bar]	4,00
Weight [Kg]	115
Tyre content 75% [litre]	179,25
Stud height [mm]	33,0
Number of studs	34x2
Zulassung	nicht notwendig
Direction bound	Yes

Hints and features:

- Narrow tyre for maintenance of row crops
- High load capacity
- Outstanding driving dynamics on the road
- Very good traction and self-cleaning
- Long service life

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.