



Hints and features:

- Wide-base tyre for mobile excavators
- · Best traction properties
- Excellent resistance

REIFEN 445 / 70 R 22.5 182 A2 / 175 A8, TL, XF (MOBILBAGGER)

Product-No.: 13375022

Technical Information:

Tyre size	445 / 70 R 22.5
TL/TT	TL
LI/SI	182 A2 / 175 A8
Tread	XF
Manufacturer	Michelin
Recom. Rim	14.00
Width [mm]	452
Outer diameter [mm]	1192
Static radius [mm]	539
Rolling circumference [mm]	3582
Rolling circumference [mm] Payload in kg at kph (1)	3582 8500 / 10
Payload in kg at kph (1)	8500 / 10
Payload in kg at kph (1) Payload in kg at kph (2)	8500 / 10 6900 / 40
Payload in kg at kph (1) Payload in kg at kph (2) Inflation pressure [bar]	8500 / 10 6900 / 40 7,50
Payload in kg at kph (1) Payload in kg at kph (2) Inflation pressure [bar] Weight [Kg]	8500 / 10 6900 / 40 7,50 120
Payload in kg at kph (1) Payload in kg at kph (2) Inflation pressure [bar] Weight [Kg] Tyre content 75% [litre]	8500 / 10 6900 / 40 7,50 120 191

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.