# Bohnenkamp Moving Professionals





#### Hints and features:

- Grass tyre with excellent contact area for low soil compaction
- Rounded tyre shoulder for optimal turf protection
- High tread pattern depth in conjunction with a rugged casing for high mileage and protection against damage (punctures)

## REIFEN 24 X 8.50 - 14 4 PR, 84 A6, TL, LG 306, RASENPROFIL ECE106

## Product-No.: 15710532

### **Technical Information:**

Tyre size	24 x 8.50 - 14
TL / TT	TL
LI / SI	84 A6
PR	4
Tread	LG 306
Manufacturer	ВКТ
Recom. Rim	7
Width [mm]	210
Outer diameter [mm]	610
Static radius [mm]	280
Rolling circumference [mm]	1769
Payload in kg at kph (1)	500 / 30
Inflation pressure [bar]	1,60
Weight [Kg]	8,85
Stud height [mm]	8,0
Zulassung	ECE 106

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes

Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.