Bohnenkamp Moving Professionals



Hints and features:

- Grass tyre with excellent contact area for low soil compaction
- Rounded tyre shoulder for optimal turf protection
- High tread pattern depth in conjunction with a rugged casing for high mileage and protection against damage (punctures)

REIFEN 31 X 15.5 - 15 4 PR, 95 A6, TL, LG 306, RASENPROFIL ECE106

Product-No.: 15710549

Technical Information:

Tyre size	31 x 15.5 - 15
TL/TT	TL
LI / SI	95 A6
PR	4
Tread	LG 306
Manufacturer	BKT
Recom. Rim	13LB
Permissible rim	13.00
Width [mm]	391
Outer diameter [mm]	792
Static radius [mm]	350
Rolling circumference [mm]	2313
Payload in kg at kph (1)	690 / 30
Inflation pressure [bar]	1,40
Weight [Kg]	23,71
Stud height [mm]	10,0
Zulassung	ECE 106

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes

Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.