



Hints and features:

- The TM 700 is an agricultural radial tyre
- It provides excellent traction in the field and maximum self-cleaning properties, comfort and very good handling on the road.
- Top-level driving performance

REIFEN 480 / 70 R 26
139 A8 / 139 B, TL, TM 700 **DA**

Product-No.: 13626194

Technical Information:

Tyre size	480 / 70 R 26
TL / TT	TL
LI / SI	139 A8 / 139 B
Tread	TM700
Manufacturer	Trelleborg
Recom. Rim	15
Permissible rim	14, 16
Width [mm]	468
Outer diameter [mm]	1358
Static radius [mm]	608
Rolling circumference [mm]	4.060
Payload in kg at kph (1)	2430 / 40
Payload in kg at kph (2)	2430 / 50
Inflation pressure [bar]	1,60
Weight [Kg]	94,5
Stud width [mm]	44
Stud height [mm]	47,0
Number of studs	17x2
Zulassung	nicht notwendig

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.