



Hints and features:

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other heavy farm machinery
- Aggressive R-1W tread pattern for maximum traction and low slip
- Offers enormous load capacities even at low inflation pressures
- Steel belts and a special stubble guard rubber compound make the tyre even tougher against punctures from corn stubble, for example

REIFEN 520 / 85 R 46
173 A8 / 169 D, TL, AGRISTAR 375
(20.8 R 46), ECE106

Product-No.: 15227430

Technical Information:

Tyre size	520 / 85 R 46
TL / TT	TL
LI / SI	173 A8 / 169 D
Tread	Agristar 375
Manufacturer	Alliance
Recom. Rim	16
Permissible rim	15, 18
Width [mm]	530
Outer diameter [mm]	2050
Static radius [mm]	941
Rolling circumference [mm]	6114
Payload in kg at kph (1)	6500 / 40
Payload in kg at kph (2)	5800 / 65
Inflation pressure [bar]	3,20
Weight [Kg]	242,58
Tyre content 75% [litre]	580
Stud width [mm]	47
Stud height [mm]	60,0
Number of studs	23x2
Zulassung	ECE 106
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.