



Hints and features:

- Bias flotation tyre for towed vehicles
- Soil-protecting tread pattern
- Also for tractors (turf rolls)

RAD 600 / 50 - 22.5 ALLIANCE FLOTATION 328
16 PR, 161 B / 157 E, TL, 10/281/335, A3, ET-100
20.00 X 22.5 TH2, RAL9006 SILBER

Product-No.: 59913524

Technical Information:

Wheel size	600 / 50 - 22.5
LI / PR	158 D / 157 E, 16 PR
Tread	Flotation 328
Manufacturer	Alliance
Rim	AG 20.00 x 22.5 TH2
Connection	10/281/335
Bolt hole execution	A3
Rim centering	BZ
ET	-100
Width [mm]	600
Outer diameter [mm]	1170
Static radius [mm]	520
Rolling circumference [mm]	3450
Inflation pressure [bar]	2,60
Loadcapacity Tyre	4250 / 65
Loadcapacity Rim	7070 / 40
Loadcapacity compl. Wheel	4625 / 50
Tread depth [mm]	25,0
Rim material	Stahl
RAL / Color	RAL9006 / Silber
Weight [Kg]	159,14

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.