



Hints and features:

- Bias flotation tyre for towed vehicles
- Soil-protecting tread pattern
- Also for tractors (turf rolls)

RAD 750 / 60 - 30.5 ALLIANCE FLOTATION 328
16 PR, 179 B / 172 D, TL, 10/281/335, A3, ET -50
24.00 X 30.5 TH2, RAL9006 SILBER

Product-No.: 59913866

Technical Information:

Wheel size	750 / 60 - 30.5
LI / PR	179 B / 172 D, 16 PR
Tread	Flotation 328
Manufacturer	Alliance
Rim	AG 24.00 x 30.5 TH2
Connection	10/281/335
Bolt hole execution	A3
Rim centering	BZ
ET	-50
Width [mm]	750
Outer diameter [mm]	1670
Static radius [mm]	720
Rolling circumference [mm]	4790
Inflation pressure [bar]	2,50
Loadcapacity Tyre	7750 / 50
Loadcapacity Rim	11220 / 40
Loadcapacity compl. Wheel	7620 / 50
Tread depth [mm]	25,0
Rim material	Stahl
RAL / Color	RAL9006 / Silber
Weight [Kg]	339,63

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.