





Hints and features:

- Popular golf tread pattern for towed vehicles
- · Gentle on the soil
- · Also for tractors and road construction

RAD 28 L - 26 ALLIANCE GOLF 330 16 PR, 173 A8, TL, 10/281/335 ET -50 DW 25 B X 26, RAL9006 SILBER

Product-No.: 59914215

Technical Information:

Wheel size	28L - 26
LI / PR	173 A8, 16 PR
Tread	330
Manufacturer	Alliance
Rim	DW 25 B x 26
Connection	10/281/335
Bolt hole execution	B3
Rim centering	BZ
ET	-50
Width [mm]	714
Outer diameter [mm]	1590
Static radius [mm]	702
Rolling circumference [mm]	4627
Inflation pressure [bar]	2,20
Loadcapacity Tyre	6500 / 40
Loadcapacity Rim	9660 / 40
Loadcapacity compl. Wheel	6500 / 40
Stud width [mm]	90
Tread depth [mm]	28,0
Rim meterial	Stahl
RAL / Color	RAL9006 / Silber
Weight [Kg]	285,15

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.