



Hints and features:

- Bias flotation tyre for towed vehicles
- Soil-protecting tread pattern
- Also for tractors (turf rolls)

RAD 600 / 55 - 22.5 ALLIANCE FLOTATION 328
16 PR, 162 D / 161 E, TL, 10/281/335, A3, ET -50
20.00 X 22.5, RAL9006 SILBER, VS H

Product-No.: 59915495

Technical Information:

Wheel size	600 / 55 - 22.5
LI / PR	162 D / 161 E, 16 PR
Tread	Flotation 328
Manufacturer	Alliance
Rim	AG 20.00 x 22.5 H2
Connection	10/281/335
Bolt hole execution	A3
Rim centering	BZ
ET	-50
Width [mm]	600
Outer diameter [mm]	1270
Static radius [mm]	550
Rolling circumference [mm]	3650
Inflation pressure [bar]	2,80
Loadcapacity Tyre	4750 / 65
Loadcapacity Rim	7600 / 40
Loadcapacity compl. Wheel	4750 / 65
Tread depth [mm]	30,0
Rim material	Stahl
RAL / Color	RAL9006 / Silber
Weight [Kg]	162,59

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.