



Hints and features:

- Bias flotation tyre for towed vehicles
- Soil-protecting tread pattern
- Also for tractors (turf rolls)

RAD 700 / 50 - 22.5 ALLIANCE FLOTATION 328
16 PR, TL, 10/281.0/335, ET-100
24.00 - 22.5 DOPPELH., *WB*

Product-No.: 59915583

Technical Information:

| | |
|----------------------------|----------------------|
| Wheel size | 700 / 50 - 22.5 |
| LI / PR | 167 D / 166 E, 16 PR |
| Tread | Flotation 328 |
| Manufacturer | Alliance |
| Rim | AG 24.00 x 22.5 TH2 |
| Connection | 10/281/335 |
| Bolt hole execution | A3 |
| Rim centering | BZ |
| ET | -100 |
| Width [mm] | 700 |
| Outer diameter [mm] | 1270 |
| Static radius [mm] | 550 |
| Rolling circumference [mm] | 3650 |
| Inflation pressure [bar] | 2,80 |
| Loadcapacity Tyre | 5450 / 65 |
| Loadcapacity Rim | 8040 / 40 |
| Loadcapacity compl. Wheel | 5300 / 70 |
| Tread depth [mm] | 25,0 |
| Rim material | Stahl |
| RAL / Color | RAL9006 / Silber |
| Weight [Kg] | 198,32 |

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.