



Hints and features:

- Bias flotation tyre for towed vehicles
- Soil-protecting tread pattern
- Also for tractors (turf rolls)

RAD 700 / 50 - 22.5 ALLIANCE FLOTATION 328
16 PR, 167 D / 166 E, TL, 10/281/335, ET -50
24.00 X 22.5, RAL9006 SILBER

Product-No.: 59915584

Technical Information:

Wheel size	700 / 50 - 22.5
LI / PR	167 D / 166 E, 16 PR
Tread	Flotation 328
Manufacturer	Alliance
Rim	AG 24.00 x 22.5 TH2
Connection	10/281/335
Bolt hole execution	A3
Rim centering	BZ
ET	-50
Width [mm]	700
Outer diameter [mm]	1270
Static radius [mm]	550
Rolling circumference [mm]	3650
Inflation pressure [bar]	2,80
Loadcapacity Tyre	5450 / 65
Loadcapacity Rim	8040 / 40
Loadcapacity compl. Wheel	5450 / 65
Tread depth [mm]	25,0
Rim material	Stahl
RAL / Color	RAL9006 / Silber
Weight [Kg]	198,32

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.