





Hints and features:

- The Nokian Forest King F2 was specially designed for use with tracks and is ideal for CTL machines
- Due to the ribbed shape of the tread pattern, the track lies firmly over the entire tread
- Special grooves in the tread centre additionally ensure the track fits firmly
- Due to the steel-reinforced casing, the tyre is perfectly protected against punctures and other damages

REIFEN 780 / 50 - 28.5 24 PR, 190 A2 / 182 A8, TT, FOREST KING F2 SF

Product-No.: 17416020

Technical Information:

Tyre size	780 / 50 - 28.5
TL/TT	TT
LI/SI	190 A2 / 182 A8
PR	24
Tread	Forest King F2
Manufacturer	Nokian
Specification	LS-2, SF
Recom. Rim	26.00
Width [mm]	780
Outer diameter [mm]	1525
Static radius [mm]	697
Rolling circumference [mm]	4618
Payload in kg at kph (1)	10600 / 10
Payload in kg at kph (2)	8500 / 40
Inflation pressure [bar]	6,00
Weight [Kg]	304,91
Zulassung	nicht notwendig
TRA Code	LS-2

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.