



REIFEN 580 / 65 R 22.5
166 D, TL, FL 630 SUPER
STEEL BELTED, ECE106

Product-No.: 15715137

Technical Information:

Tyre size	580 / 65 R 22.5
TL / TT	TL
LI / SI	166 D
Tread	FL 630 Super
Manufacturer	BKT
Specification	Steel Belted
Recom. Rim	AG18.00
Permissible rim	AG16.00, AG17.00, AG20.00
Width [mm]	577
Outer diameter [mm]	1326
Static radius [mm]	594
Rolling circumference [mm]	4058
Payload in kg at kph (1)	5300 / 65
Inflation pressure [bar]	4,00
Weight [Kg]	125,92
Stud height [mm]	24,5
Number of studs	23x2
Zulassung	ECE 106

Hints and features:

- Flotation tyre with steel belt reinforcement for use on slurry tankers, manure spreaders and similar towed agricultural vehicles
- Designed more for use in fields and on arable land
- Optimised tread pattern, larger contact area between lugs and ground for smoother driving
- Extreme puncture resistance

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.