

BRIDGESTONE



REIFEN VF 650 / 85 R 38
179 D / 176 E, TL, VT TRACTOR

Product-No.: 10629078

Technical Information:

Tyre size	VF 650 / 85 R 38
TL / TT	TL
LI / SI	179 D / 176 E
Tread	VT Tractor
Manufacturer	Bridgestone
Recom. Rim	23
Permissible rim	21, 20
Width [mm]	663
Outer diameter [mm]	2071
Static radius [mm]	875
Rolling circumference [mm]	6027
Payload in kg at kph (1)	7750 / 65
Payload in kg at kph (2)	7100 / 70
Inflation pressure [bar]	1,60
Weight [Kg]	335,8
Tyre content 75% [litre]	839,25
Stud height [mm]	61,0
Number of studs	22x2
Zulassung	nicht notwendig
Tyre technology	VF
Direction bound	Yes

Hints and features:

- High load capacity thanks to VF-Ultraflex technology
- Low tyre pressure, even with heavy loads
- Very good traction und high ride comfort
- Thanks to NRO technology (Narrow Rim Option), the tyre can be mounted on a narrower rim than other VF or IF tyres of the same dimension.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.