

BRIDGESTONE



REIFEN VF 900 / 60 R 38 NRO
183 D / 180 E, TL, VT TRACTOR

Product-No.: 10629084

Technical Information:

Tyre size	VF 900 / 60 R 38 NRO
TL / TT	TL
LI / SI	183 D / 180 E
Tread	VT Tractor
Manufacturer	Bridgestone
Recom. Rim	30
Permissible rim	28
Width [mm]	851
Outer diameter [mm]	2045
Static radius [mm]	876
Rolling circumference [mm]	6026
Payload in kg at kph (1)	8750 / 65
Payload in kg at kph (2)	8000 / 70
Inflation pressure [bar]	1,60
Weight [Kg]	335,8
Tyre content 75% [litre]	1.065
Stud height [mm]	65,0
Number of studs	18x2
Zulassung	nicht notwendig
NRO	NRO
Tyre technology	VF
Direction bound	Yes

Hints and features:

- High load capacity thanks to VF-Ultraflex technology
- Low tyre pressure, even with heavy loads
- Very good traction und high ride comfort
- Thanks to NRO technology (Narrow Rim Option), the tyre can be mounted on a narrower rim than other VF or IF tyres of the same dimension.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.