



#### Hints and features:

- The Alliance Forestry 360 is a forestry tyre for light forestry applications
- Its low lug angles provide excellent traction
- Due to the strong nylon casing with steel breakers, high undertread gauge and reinforced sidewalls and tread pattern, the tyre is particularly robust
- The tyre can also be used for agro-industrial applications

REIFEN 650 / 65 R 42  
172 A2 / 165 A8, TL, FORESTRY 360  
STEEL BELTED, ECE106

**Product-No.: 15226818**

#### Technical Information:

Tyre size	650 / 65 R 42
TL / TT	TL
LI / SI	172 A2 / 165 A8
Tread	Forestry 360
Manufacturer	Alliance
Specification	R1-W, Steel Belted
Recom. Rim	20
Permissible rim	18
Width [mm]	655
Outer diameter [mm]	1950
Static radius [mm]	900
Rolling circumference [mm]	5869
Payload in kg at kph (1)	6300 / 10
Payload in kg at kph (2)	5150 / 40
Inflation pressure [bar]	2,40
Weight [Kg]	285,8
Tyre content 75% [litre]	670,5
Stud height [mm]	52,0
Number of studs	24x2
Zulassung	ECE 106
TRA Code	R1-W

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.