



REIFEN 12.5 / 80 - 18  
16 PR, 135 A8 / 148 A8, TL, AS 504  
ECE106

**Product-No.: 15711935**

## Technical Information:

Tyre size	12.5 / 80 - 18
TL / TT	TL
LI / SI	135 A8 / 148 A8
PR	16
Tread	AS 504
Manufacturer	BKT
Recom. Rim	9
Permissible rim	11
Width [mm]	308
Outer diameter [mm]	987
Static radius [mm]	438
Rolling circumference [mm]	2892
Payload in kg at kph (1)	2180 / 40
Payload in kg at kph (2)	3150 / 40
Inflation pressure [bar]	4,90
Weight [Kg]	42,97
Stud height [mm]	28,0
Zulassung	ECE 106
Direction bound	Yes

## Hints and features:

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes

Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.