





Hints and features:

- Ideal in the most varying conditions, reliable throughout the whole year
- High level of directional stability in onroad and off-road applications
- The tread pattern ensures rapid selfcleaning for a clean road surface
- · Designed for exceptional durability
- Environmentally friendly: manufactured without polluting aromatic oils.
 Exemplary low rolling resistance reduces fuel consumption

REIFEN 360 / 70 R 20 136 A8 / 131 D, TL, TRI 2, M+S

Product-No.: 17426015

Technical Information:

Tyre size	360 / 70 R 20
TL / TT	TL
LI/SI	136 A8 / 131 D
Tread	TRI 2
Manufacturer	Nokian
Specification	M+S
Recom. Rim	11
Permissible rim	10, 12
Width [mm]	357
Outer diameter [mm]	1028
Static radius [mm]	469
Static radius [mm] Rolling circumference [mm]	469 3104
Rolling circumference [mm]	3104
Rolling circumference [mm] Payload in kg at kph (1)	3104 2240 / 40
Rolling circumference [mm] Payload in kg at kph (1) Payload in kg at kph (2)	3104 2240 / 40 1950 / 65
Rolling circumference [mm] Payload in kg at kph (1) Payload in kg at kph (2) Inflation pressure [bar]	3104 2240 / 40 1950 / 65 3,20
Rolling circumference [mm] Payload in kg at kph (1) Payload in kg at kph (2) Inflation pressure [bar] Weight [Kg]	3104 2240 / 40 1950 / 65 3,20 59,92
Rolling circumference [mm] Payload in kg at kph (1) Payload in kg at kph (2) Inflation pressure [bar] Weight [Kg] Stud height [mm]	3104 2240 / 40 1950 / 65 3,20 59,92 26,0

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.