





Hints and features:

- New radial tyre for high-power tractors over 250 hp. Thanks to Speed Index E, this tyre allows high payloads at speeds of up to 70 km/h
- The constant and uniform contact area reduces rolling resistance and fuel consumption
- Excellent ride comfort due to flexible sidewalls
- The special casing design with 6 polyester belts provides superb stability on the road and in the field
- A new sidewall compound and improved bead result in perfect heat dissipation

REIFEN 710 / 70 R 38 171 D / 168 E, TL, AGRIMAX SIRIO HIGH SPEED, ECE106

Product-No.: 15726951

## **Technical Information:**

Tyre size	710 / 70 R 38
TL/TT	TL
LI/SI	171 D / 168 E
Tread	Agrimax Sirio
Manufacturer	BKT
Specification	High Speed
Recom. Rim	DW23B
Permissible rim	DW25B
Width [mm]	716
Outer diameter [mm]	1959
Static radius [mm]	887
Rolling circumference [mm]	5840
Payload in kg at kph (1)	6150 / 65
Payload in kg at kph (2)	5600 / 70
Inflation pressure [bar]	2,40
Weight [Kg]	306
Stud width [mm]	55
Stud height [mm]	62,0
Number of studs	20x2
Zulassung	ECE 106
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.