



Hints and features:

- Radial multipurpose tyre for a wide variety of applications
- Agricultural tractor pattern for good traction when operating on arable land
- High load capacities even with low inflation pressures
- Radial textile-casing with steel-belt reinforcement

REIFEN 460 / 70 R 24
159 A8 / 159 B, TL, 570
(17.5 LR 24), ECE106

Product-No.: 15226012

Technical Information:

Tyre size	460 / 70 R 24
TL / TT	TL
LI / SI	159 A8 / 159 B
Tread	570
Manufacturer	Alliance
Recom. Rim	15
Permissible rim	14
Width [mm]	445
Outer diameter [mm]	1245
Static radius [mm]	564
Rolling circumference [mm]	3682
Payload in kg at kph (1)	4375 / 40
Payload in kg at kph (2)	4375 / 50
Inflation pressure [bar]	4,00
Weight [Kg]	91,2
Stud height [mm]	36,9
Number of studs	19x2
Zulassung	ECE 106
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes

Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.