



## Hints and features:

- The Alliance 372 is an IF tyre for high-performance tractors from approx. 220 hp
- Its extremely flexible sidewalls enable it to carry up to 20% more load capacity at the same inflation pressure or the same load capacity at 20% lower inflation pressure compared with a standard tyre
- The larger contact area provides excellent traction and consequently reduced fuel costs
- At the same time, soil compaction is reduced and the soil optimally protected
- The R-1W tread pattern ensures excellent grip and a long service life
- The tyre can be used for cyclic field operation (CFO) on harvesters

REIFEN IF 620 / 75 R 30 CFO  
164 D, TL, AGRIFLEX 372  
STEEL BELTED, ECE106

**Product-No.: 15225157**

## Technical Information:

Tyre size	IF 620 / 75 R 30 CFO
TL / TT	TL
LI / SI	164 D
Tread	Agriflex 372
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	DW23B
Permissible rim	DW21B, DW20B
Width [mm]	650
Outer diameter [mm]	1675
Static radius [mm]	734
Rolling circumference [mm]	4879
Payload in kg at kph (1)	5000 / 65
Inflation pressure [bar]	1,60
Weight [Kg]	215,95
Tyre content 75% [litre]	589
Stud height [mm]	58,0
Number of studs	20x2
Zulassung	ECE 106
Cyclic field use	CFO
Tyre technology	IF
Direction bound	Yes