



REIFEN VF 480 / 80 R 50  
171 D, TL, AGRIFLEX 354 +  
STEEL BELTED, ECE106

**Product-No.: 15226683**

#### Technical Information:

|                            |                  |
|----------------------------|------------------|
| Tyre size                  | VF 480 / 80 R 50 |
| TL / TT                    | TL               |
| LI / SI                    | 171 D            |
| Tread                      | Agriflex 354 +   |
| Manufacturer               | Alliance         |
| Specification              | Steel Belted     |
| Recom. Rim                 | DW16             |
| Permissible rim            | DW15             |
| Width [mm]                 | 479              |
| Outer diameter [mm]        | 2050             |
| Static radius [mm]         | 936              |
| Rolling circumference [mm] | 6114             |
| Payload in kg at kph (1)   | 6150 / 65        |
| Inflation pressure [bar]   | 2,40             |
| Weight [Kg]                | 212,15           |
| Tyre content 75% [litre]   | 494              |
| Stud height [mm]           | 52,0             |
| Number of studs            | 30x2             |
| Zulassung                  | ECE 106          |
| Tyre technology            | VF               |
| Direction bound            | Yes              |

#### Hints and features:

- The Alliance Agriflex 354 is a row crop tyre with VF technology for tractors, self-propelled and towed field sprayers
- As a VF tyre, it has 40% more load capacity at the same inflation pressure or the same load capacity at 40% lower inflation pressure compared with a standard tyre
- This leads to optimal crop and soil protection
- The tyre provides high traction and excellent self-cleaning properties thanks to the stronger and optimally shaped lugs
- Its large contact area and steel belted construction also ensure traction and good ground pressure distribution
- The tyre is characterised by durability, reduced fuel costs and ride comfort