





Hints and features:

- The AC 85 is a modern, all-round standard tyre for a wide work spectrum in the field and on the road
- Its tread pattern provides excellent traction
- Thanks to its enlarged contact area, the tyre is also suitable for work on grassland
- The wear-resistant tread compound ensures a long service life

REIFEN 340 / 85 R 38 133 A8 / 133 B, TL, AC 85

Product-No.: 10928110

## **Technical Information:**

Tyre size	340 / 85 R 38
TL/TT	TL
LI/SI	133 A8 / 133 B
Tread	AC 85
Manufacturer	Mitas
Recom. Rim	12
Permissible rim	11
Width [mm]	365
Outer diameter [mm]	1562
Static radius [mm]	719
Rolling circumference [mm]	4685
Rolling circumference [mm] Payload in kg at kph (1)	4685 2060 / 40
Payload in kg at kph (1)	2060 / 40
Payload in kg at kph (1) Payload in kg at kph (2)	2060 / 40 2060 / 50
Payload in kg at kph (1) Payload in kg at kph (2) Inflation pressure [bar]	2060 / 40 2060 / 50 1,60
Payload in kg at kph (1) Payload in kg at kph (2) Inflation pressure [bar] Weight [Kg]	2060 / 40 2060 / 50 1,60 82,8
Payload in kg at kph (1) Payload in kg at kph (2) Inflation pressure [bar] Weight [Kg] Stud width [mm]	2060 / 40 2060 / 50 1,60 82,8 37
Payload in kg at kph (1) Payload in kg at kph (2) Inflation pressure [bar] Weight [Kg] Stud width [mm] Stud height [mm]	2060 / 40 2060 / 50 1,60 82,8 37 40,0

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.