


TRELLEBORG



REIFEN 200 / 90 - 16
8 PR, 111 A8, TL, AF302
(7.00-16)

Product-No.: 19011370

Technical Information:

Tyre size	200 / 90 - 16
TL / TT	TL
LI / SI	111 A8
PR	8
Tread	AF302
Manufacturer	Trelleborg
Recom. Rim	5.00
Width [mm]	204
Outer diameter [mm]	764
Static radius [mm]	338
Rolling circumference [mm]	2227
Payload in kg at kph (1)	1090 / 40
Inflation pressure [bar]	2,40
Weight [Kg]	12,3
Zulassung	nicht notwendig

Hints and features:

- Implement tyre with metric size designation for trailers and other agricultural machinery such as spreaders, balers, ploughs, seed drills, etc.
- Improved load capacity and increased maximum speed (40 km/h)
- Tread pattern design and rounded shoulder area ensure soil protection in fields and low rolling resistance on the road

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.