## Bohnenkamp Moving Professionals



## Hints and features:

- Implement tyre with metric size designation for trailers and other agricultural machinery such as spreaders, balers, ploughs, seed drills, etc.
- Improved load capacity and increased maximum speed (40 km/h)
- Tread pattern design and rounded shoulder area ensure soil protection in fields and low rolling resistance on the road

REIFEN 210 / 95 - 16 10 PR, 120 A8, TL, AF302 (7.50-16)

## Product-No.: 19011410

## **Technical Information:**

Tyre size	210 / 95 - 16
TL/TT	TL
LI / SI	120 A8
PR	10
Tread	AF302
Manufacturer	Trelleborg
Recom. Rim	5.50
Width [mm]	218
Outer diameter [mm]	802
Static radius [mm]	347
Rolling circumference [mm]	2392
Payload in kg at kph (1)	1400 / 40
Inflation pressure [bar]	2,80
Weight [Kg]	15,13
Zulassung	nicht notwendig

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.