





Hints and features:

- The HC 70 is an all-round wide-base tyre with increased loading capacity
- Its tread pattern provides excellent traction
- Due to rounded lug edges and a round shoulder design, the soil is effectively protected, particularly during work on grassland
- The wide tyre shoulder guarantees excellent ride comfort on the road
- Economical operational costs thanks to minimised slip

REIFEN 380 / 70 R 24 128 A8 / 125 D, TL, HC 70

Product-No.: 10927665

Technical Information:

Tyre size	380 / 70 R 24
TL/TT	TL
LI/SI	128 A8 / 125 D
Tread	HC 70
Manufacturer	Mitas
Recom. Rim	12
Permissible rim	11, 13
Width [mm]	395
Outer diameter [mm]	1191
Static radius [mm]	533
Rolling circumference [mm]	3545
Payload in kg at kph (1)	1800 / 40
Payload in kg at kph (2)	1650 / 65
Inflation pressure [bar]	1,60
Weight [Kg]	69,2
Stud height [mm]	40,0
Number of studs	18x2
Zulassung	nicht notwendig
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.