Bohnenkamp Moving Professionals

Mitas



Hints and features:

- The AC 85 is a modern, all-round standard tyre for a wide work spectrum in the field and on the road
- Its tread pattern provides excellent traction
- Thanks to its enlarged contact area, the tyre is also suitable for work on grassland
- The wear-resistant tread compound ensures a long service life

REIFEN 520 / 85 R 46 158 A8 / 158 B, TL, AC 85 (20.8 R 46)

Product-No.: 10928270

Technical Information:

Tyre size	520 / 85 R 46
TL / TT	5207 03 K 40
. = /	. =
LI / SI	158 A8 / 158 B
Tread	AC 85
Manufacturer	Mitas
Recom. Rim	16
Permissible rim	18
Width [mm]	545
Outer diameter [mm]	2043
Static radius [mm]	930
Rolling circumference [mm]	6131
Payload in kg at kph (1)	4250 / 40
Payload in kg at kph (2)	4250 / 50
Inflation pressure [bar]	1,60
Weight [Kg]	212,2
Stud height [mm]	54,0
Number of studs	23x2
Zulassung	nicht notwendig
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.