

## Mitas



## Hints and features:

- The AC 65 is a powerful all-round wide tyre for use in the field and on the road
- Thanks to its wide contact area, the soil is protected effectively
- The wear-resistant rubber compound ensures a long service life
- The tyre is characterised by a large air volume, guaranteeing a high transport performance

REIFEN 540 / 65 R 24 143 A8 / 140 D, TL, AC 65

Product-No.: 10927750

## **Technical Information:**

Tyre size	540 / 65 R 24
TL / TT	TL
LI/SI	143 A8 / 140 D
Tread	AC 65
Manufacturer	Mitas
Recom. Rim	16
Permissible rim	18, 15
Width [mm]	523
Outer diameter [mm]	1317
Static radius [mm]	590
Rolling circumference [mm]	3922
Payload in kg at kph (1)	2725 / 40
Payload in kg at kph (2)	2500 / 65
Inflation pressure [bar]	1,60
Weight [Kg]	99,4
Stud width [mm]	41
Stud height [mm]	45,0
Number of studs	19x2
Zulassung	nicht notwendig
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.