Bohnenkamp Moving Professionals

CARLISLE



Hints and features:

- Special tyre for professional lawn and landscape maintenance
- Offers very good flotation properties due to a flat contact area and reduced tread gaps
- Low soil pressure and good traction at the same time

REIFEN 24 X 13.00 B 12 6 PR, 109 A4, TL, ULTRA TRAC (320/45B12), ECE106

Product-No.: 12598018

Technical Information:

	24 x 13.00 B 12
Tyre size	
TL/TT	TL
LI / SI	109 A4
PR	6
Tread	Ultra Trac
Manufacturer	Carlisle
Recom. Rim	10.50
Permissible rim	10.501
Width [mm]	327
Outer diameter [mm]	593
Static radius [mm]	265
Rolling circumference [mm]	1766
Payload in kg at kph (1)	1030 / 20
Inflation pressure [bar]	1,93
Weight [Kg]	12,7
Stud height [mm]	6,9
Zulassung	ECE 106

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.