

KENDA



Hints and features:

- Versatile and reliable high-speed car trailer tyre

REIFEN 155 / 70 R 12 C
104 / 101 N, TL, KR16 KARGO PRO, M+S

Product-No.: 19266074

Technical Information:

Tyre size	155 / 70 R 12 C
TL / TT	TL
LI / SI	104 / 101 N
Tread	KR16 Kargo Pro
Manufacturer	Kenda
Specification	M+S
Recom. Rim	4J
Width [mm]	152
Outer diameter [mm]	523
Static radius [mm]	240
Rolling circumference [mm]	1598
Payload in kg at kph (1)	900 / 140
Loadcapacity Twin Truck	825 / 140
Inflation pressure [bar]	6,50
Weight [Kg]	7
Rolling resistance	D
Wet grip	C
Rolling Noise DB	70
Rolling Noise Level	B
Zulassung	ECE 54, ECE 117
M+S	M+S

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.