



Hints and features:

- The KARGO MAX ST-4000 achieves a high mileage and is especially suited to commercial trailers
- These tyres are approved exclusively for trailer usage

REIFEN 195 / 65 R 15 95 N, TL, KARGOMAX ST 4000, M+S

Product-No.: 19866032

Technical Information:

Tyre size	195 / 65 R 15
TL/TT	TL
LI/SI	95 N
Tread	KargoMax ST 4000
Manufacturer	GT Radial
Specification	M+S
Recom. Rim	6
Width [mm]	201
Outer diameter [mm]	635
Static radius [mm]	290
Rolling circumference [mm]	1937
Rolling circumference [mm] Payload in kg at kph (1)	1937 690 / 140
Payload in kg at kph (1)	690 / 140
Payload in kg at kph (1) Inflation pressure [bar]	690 / 140 3,00
Payload in kg at kph (1) Inflation pressure [bar] Weight [Kg]	690 / 140 3,00 9,49
Payload in kg at kph (1) Inflation pressure [bar] Weight [Kg] Rolling resistance	690 / 140 3,00 9,49 C
Payload in kg at kph (1) Inflation pressure [bar] Weight [Kg] Rolling resistance Wet grip	690 / 140 3,00 9,49 C
Payload in kg at kph (1) Inflation pressure [bar] Weight [Kg] Rolling resistance Wet grip Rolling Noise DB	690 / 140 3,00 9,49 C C

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.