

KENDA

■ ■ ● Bohnenkamp



Hints and features:

- The Kenda K592 Bearclaw EVO is a versatile ATV tyre for the use on all kinds of terrain
- The tread pattern with big centre lugs provides improved directional stability and good braking traction
- Dimpled lugs provide a very good grip on rain-soaked slopes
- The shoulder lugs ensure perfect cornering
- Despite its low weight, the tyre provides exceptional puncture resistance

REIFEN AT 26 X 9 - 14
6 PR, 48 N, TL, K592 BEARCLAW EVO
***, (235/65-14), ECE75

Product-No.: 19210210

Technical Information:

| | |
|----------------------------|-------------------|
| Tyre size | AT 26 x 9 - 14 |
| TL / TT | TL |
| LI / SI | 48 N |
| PR | 6 |
| Tread | K592 Bearclaw EVO |
| Manufacturer | Kenda |
| Specification | *** |
| Recom. Rim | 7.0 |
| Permissible rim | 7.00, 7.50 |
| Width [mm] | 220 |
| Outer diameter [mm] | 660 |
| Static radius [mm] | 305 |
| Rolling circumference [mm] | 2005 |
| Payload in kg at kph (1) | 180 / 140 |
| Inflation pressure [bar] | 0,50 |
| Weight [Kg] | 10,16 |
| Stud height [mm] | 18,5 |
| Zulassung | ECE 75 |
| Star Rating | *** |
| Tyre technology | AT |
| Direction bound | Yes |

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.