





Hints and features:

- The Traxion XXL was developed for tractors with an engine performance above 160 hp
- Its special tread pattern and flexible casing provide a large contact area and thus even ground pressure distribution
- The large tyre volume enables a high load capacity at low inflation pressure
- In field applications, the tyre offers excellent traction
- In transport journeys, it distinguishes itself through high ride comfort and safety at speeds up to 70 km/h

REIFEN 600 / 65 R 28 154 D, TL, TRAXION XXL ECE106

Product-No.: 14826040

Technical Information:

Tyre size	600 / 65 R 28
TL/TT	TL
LI/SI	154 D
Tread	TRAXION XXL
Manufacturer	Vredestein
Recom. Rim	18
Permissible rim	20
Width [mm]	610
Outer diameter [mm]	1480
Static radius [mm]	670
Rolling circumference [mm]	4400
Payload in kg at kph (1)	3750 / 65
Inflation pressure [bar]	2,40
Weight [Kg]	177,38
Tyre content 75% [litre]	370
Stud height [mm]	50,4
Zulassung	ECE 106
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.