

Firestone



REIFEN 600 / 65 R 34
151 D / 148 E, TL, MAXI TRACTION 65

Product-No.: 10627202

Technical Information:

Tyre size	600 / 65 R 34
TL / TT	TL
LI / SI	151 D / 148 E
Tread	Maxi Traction 65
Manufacturer	Firestone
Recom. Rim	18
Permissible rim	20
Width [mm]	590
Outer diameter [mm]	1639
Static radius [mm]	737
Rolling circumference [mm]	4923
Payload in kg at kph (1)	3450 / 65
Payload in kg at kph (2)	3150 / 70
Inflation pressure [bar]	1,60
Weight [Kg]	170,03
Tyre content 75% [litre]	463,5
Stud height [mm]	53,5
Number of studs	20x2
Zulassung	nicht notwendig
Direction bound	Yes

Hints and features:

- Agricultural tyre for high-performance tractors
- Very good traction in fields
- Excellent ride comfort on the road
- Very low soil compaction

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.