



Hints and features:

- The Nokian Logger King LS-2 was specially developed for skidders working in the toughest conditions
- Due to its strong, high-strength and steel-reinforced casing in the tread and shoulder area, the tyre is particularly resistant to damages
- The particularly hard-wearing rubber compound is ideal for demanding forestry use
- The structure of the tyre bead with a seamless circumferential steel core enables easier mounting and even pressure distribution on the rim flange
- The rubber compound in the bead area reduces the possibility of tyre slip to a minimum

REIFEN 24.5 - 32 20 PR, 169 A6, TL, LOGGER KING LS-2 SF

Product-No.: 17421950

Technical Information:

Tyre size	24.5 - 32
TL / TT	TL
LI / SI	169 A6
PR	20
Tread	Logger King LS-2
Manufacturer	Nokian
Specification	LS-2, SF
Recom. Rim	21
Width [mm]	622
Outer diameter [mm]	1831
Static radius [mm]	835
Rolling circumference [mm]	5454
Payload in kg at kph (1)	5800 / 30
Payload in kg at kph (2)	8200 / 10
Inflation pressure [bar]	3,10
Weight [Kg]	333,21
Tyre content 75% [litre]	615
Stud height [mm]	58,0
Number of studs	18x2
Zulassung	nicht notwendig
TRA Code	LS-2