



Hints and features:

- The Nokian Logger King LS-2 was specially developed for skidders working in the toughest conditions
- Due to its strong, high-strength and steel-reinforced casing in the tread and shoulder area, the tyre is particularly resistant to damages
- The particularly hard-wearing rubber compound is ideal for demanding forestry use
- The structure of the tyre bead with a seamless circumferential steel core enables easier mounting and even pressure distribution on the rim flange
- The rubber compound in the bead area reduces the possibility of tyre slip to a minimum

REIFEN 30.5 L - 32 20 PR, 170 A6, TL, LOGGER KING LS-2 SF

Product-No.: 17421960

Technical Information:

Tyre size	30.5 L - 32
TL / TT	TL
LI / SI	170 A6
PR	20
Tread	Logger King LS-2
Manufacturer	Nokian
Specification	LS-2, SF
Recom. Rim	27
Width [mm]	775
Outer diameter [mm]	1847
Static radius [mm]	824
Rolling circumference [mm]	5529
Payload in kg at kph (1)	6000 / 30
Payload in kg at kph (2)	8400 / 10
Inflation pressure [bar]	2,40
Weight [Kg]	409,22
Tyre content 75% [litre]	780
Stud height [mm]	67,0
Number of studs	16x2
Zulassung	nicht notwendig
TRA Code	LS-2