



REIFEN IF 320 / 105 R 54
167 D, TL, AGRIFLEX 354
STEEL BELTED, ECE106

Product-No.: 15226726

Technical Information:

Tyre size	IF 320 / 105 R 54
TL / TT	TL
LI / SI	167 D
Tread	Agriflex 354
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	11
Permissible rim	10, 12
Width [mm]	330
Outer diameter [mm]	2040
Static radius [mm]	959
Rolling circumference [mm]	6230
Payload in kg at kph (1)	5450 / 65
Inflation pressure [bar]	4,40
Weight [Kg]	151
Tyre content 75% [litre]	244,5
Stud height [mm]	47,0
Number of studs	37x2
Zulassung	ECE 106
Tyre technology	IF
Direction bound	Yes

Hints and features:

- The Alliance Agriflex 354 is a row crop tyre with IF technology for tractors, self-propelled and towed field sprayers
- As an IF tyre, it has 20% more load capacity at the same inflation pressure or the same load capacity at 20% lower inflation pressure compared with a standard tyre
- This leads to optimal crop and soil protection
- The tyre provides high traction and excellent self-cleaning properties thanks to the stronger and optimally shaped lugs
- Its large contact area and steel belt construction also ensure traction and good ground pressure distribution
- The tyre is characterised by durability, reduced fuel costs and ride comfort