Bohnenkamp Moving Professionals



Hints and features:

- The Alliance 885 was developed for balers, grain wagons, cultivators, small agricultural trailers and similar towed vehicles
- The rounded tyre shoulder and large contact area protect crops and soil from damage
- The large lugs in the middle of the tread provide comfortable handling during transport journeys
- Its low rolling resistance reduces fuel consumption
- Thanks to the reinforced sidewall and the strong casing with steel belts, the tyre is optimally protected against damages

REIFEN 750 / 45 R 26.5 170 D, TL, 885 STEEL BELTED, ECE106

Product-No.: 15216257

Technical Information:

Tyre size	750 / 45 R 26.5
TL / TT	TL
LI / SI	170 D
Tread	885
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	24.00
Width [mm]	740
Outer diameter [mm]	1360
Static radius [mm]	618
Rolling circumference [mm]	4138
Payload in kg at kph (1)	6000 / 65
Inflation pressure [bar]	4,00
Weight [Kg]	170,55
Stud height [mm]	26,0
Number of studs	21x2
Zulassung	ECE 106
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.