



Hints and features:

- MPT radial tyre for off-road transport applications, suitable for fertiliser spreaders, sprayers, dumpers and agricultural trailers
- Very good self-cleaning due to wide interspaces in the tread
- The tyre provides soil protection and flotation tyre characteristics in the field
- The special non-directional tread pattern enables equal traction in the field and good driving comfort on short road distances
- Its unique high-speed steel-belted construction and its special rubber compound permit speeds up to 100 km/h for road applications
- All-steel carcass with continuous steel insert plus 3 steel belt layers for maximum demands and workloads

RAD 600 / 50 R 22.5 ALLIANCE 380
164 J, TL, 10/281/335, A3, ET -50
20.00 X 22.5, RAL9006 SILBER, VS H, ALL
STEEL

Product-No.: 59913561

Technical Information:

Wheel size	600 / 50 R 22.5
LI / PR	164 J
Tread	380
Manufacturer	Alliance
Rim	AG 20.00 x 22.5 H2
Connection	10/281/335
Bolt hole execution	A3
Rim centering	BZ
ET	-50
Width [mm]	608
Outer diameter [mm]	1172
Static radius [mm]	527
Rolling circumference [mm]	3611
Inflation pressure [bar]	6,50
Loadcapacity Tyre	5000 / 100
Loadcapacity Rim	5000 / 100
Loadcapacity compl. Wheel	5000 / 100
Tread depth [mm]	25,0
Rim material	Stahl
RAL / Color	RAL9006 / Silber
Weight [Kg]	195,86