

**Kleber**



■ ■ ■ Bohnenkamp

REIFEN 230 / 95 R 48  
139 A8 / 136 D, TL, CROPKER  
(9.5 R 48)

**Product-No.: 12426819**

#### Technical Information:

Tyre size	230 / 95 R 48
TL / TT	TL
LI / SI	139 A8 / 136 D
Tread	Cropker
Manufacturer	Kleber
Recom. Rim	7
Permissible rim	8
Width [mm]	224
Outer diameter [mm]	1659
Static radius [mm]	786
Rolling circumference [mm]	4989
Payload in kg at kph (1)	2430 / 40
Payload in kg at kph (2)	2240 / 65
Inflation pressure [bar]	4,00
Weight [Kg]	55
Tyre content 75% [litre]	109
Stud height [mm]	31,0
Number of studs	34x2
Zulassung	nicht notwendig
Direction bound	Yes

#### Hints and features:

- The Kleber Cropker is a premium crop tyre for tractors in the 80-200 hp performance range
- Compared with its predecessor, the Kleber Super 3, the Cropker offers a higher load capacity and the double identifier D/A8
- It can be used as a FRT (Free Rolling Tyre) on towed vehicles with a load surcharge of up to 20% at 40 km/h
- Thanks to the special root-friendly lug shoulders, plants in row crops are optimally protected
- Its tread pattern reinforced in the centre of the tread provides improved driving and steering precision and longer mileage
- Due to the shape of the lugs and the spaces between them, the tyre offers very good self-cleaning properties