Bohnenkamp

📕 🛑 Moving Professionals



Hints and features:

- The Kleber Cropker is a premium crop tyre for tractors in the 80-200 hp performance range
- · Compared with its predecessor, the Kleber Super 3, the Cropker offers a higher load capacity and the double identifier D/A8
- · It can be used as a FRT (Free Rolling Tyre) on towed vehicles with with a load surcharge of up to 20% at 40 km/h
- · Thanks to the special root-friendly lug shoulders, plants in row crops are optimally protected
- · Its tread pattern reinforced in the centre of the tread provides improved driving and steering precision and longer mileage
- Due to the shape of the lugs and the spaces between them, the tyre offers very good self-cleaning properties

REIFEN 270 / 95 R 48 147 A8 / 144 D, TL, CROPKER (11.2 R 48)

Product-No.: 12426822

Technical Information:

Tyre size	270 / 95 R 48
TL / TT	TL
LI / SI	147 A8 / 144 D
Tread	Cropker
Manufacturer	Kleber
Recom. Rim	9
Permissible rim	8, 10
Width [mm]	277
Outer diameter [mm]	1736
Static radius [mm]	819
Rolling circumference [mm]	5217
Payload in kg at kph (1)	3075 / 40
Payload in kg at kph (2)	2800 / 65
Inflation pressure [bar]	4,00
Weight [Kg]	72
Tyre content 75% [litre]	130
Stud height [mm]	34,0
Number of studs	30x2
Zulassung	nicht notwendig
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.