



Hints and features:

- The Alliance 372 is an IF tyre for high-performance tractors from approx. 220 hp
- Its extremely flexible sidewalls enable it to carry up to 20% more load capacity at the same inflation pressure or the same load capacity at 20% lower inflation pressure compared with a standard tyre
- The larger contact area provides excellent traction and consequently reduced fuel costs
- At the same time, soil compaction is reduced and the soil optimally protected
- The R-1W tread pattern ensures excellent grip and a long service life
- The tyre can be used for cyclic field operation (CFO) on harvesters

REIFEN IF 650 / 75 R 30 CFO
166 D, TL, AGRIFLEX 372
STEEL BELTED, ECE106

Product-No.: 15225161

Technical Information:

Tyre size	IF 650 / 75 R 30 CFO
TL / TT	TL
LI / SI	166 D
Tread	Agriflex 372
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	DW23B
Permissible rim	21
Width [mm]	662
Outer diameter [mm]	1717
Static radius [mm]	748
Rolling circumference [mm]	5007
Payload in kg at kph (1)	5300 / 65
Inflation pressure [bar]	1,60
Weight [Kg]	236,29
Tyre content 75% [litre]	652,5
Stud height [mm]	56,0
Zulassung	ECE 106
Cyclic field use	CFO
Tyre technology	IF
Direction bound	Yes