



REIFEN 560 / 45 R 22.5
163 A8 / 152 D, TL, FL 630 ULTRA
(550/45 R 22.5), ECE106

Product-No.: 15715113

Technical Information:

Tyre size	560 / 45 R 22.5
TL / TT	TL
LI / SI	163 A8 / 152 D
Tread	FL 630 Ultra
Manufacturer	BKT
Recom. Rim	AG16.00
Width [mm]	543
Outer diameter [mm]	1076
Static radius [mm]	490
Rolling circumference [mm]	3290
Payload in kg at kph (1)	4875 / 40
Payload in kg at kph (2)	3550 / 65
Inflation pressure [bar]	4,00
Weight [Kg]	91,7
Tyre content 75% [litre]	247
Stud height [mm]	28,5
Number of studs	18x2
Zulassung	ECE 106

Hints and features:

- The BKT FL630 Ultra is a flotation tyre for use in the field and on the road
- It is mostly suitable for agricultural trailers, balers, heavy seeders and manure spreaders
- The robust tread pattern provides excellent traction even when cornering and manoeuvring
- The tyre guarantees good grip on all kinds of surfaces and has very good self-cleaning properties
- Its large contact area ensures very low soil compaction and optimum soil protection
- When driving on the road, the tyre is characterised by high ride comfort and low noise emission