Bohnenkamp Moving Professionals



Hints and features:

- The Alliance 372 is an IF tyre for highperformance tractors from approx. 220 hp
- Its extremely flexible sidewalls enable it to carry up to 20% more load capacity at the same inflation pressure or the same load capacity at 20% lower inflation pressure compared with a standard tyre
- The larger contact area provides excellent traction and consequently reduced fuel costs
- At the same time, soil compaction is reduced and the soil optimally protected
- The R-1W tread pattern ensures excellent grip and a long service life
- The tyre can be used for cyclic field operation (CFO) on harvesters

REIFEN IF 520 / 80 R 26 CFO 165 A8, TL, AGRIFLEX 372 STEEL BELTED, ECE106

Product-No.: 15225087

Technical Information:

Tyre size	IF 520 / 80 R 26 CFO
TL/TT	TL
LI / SI	165 A8
Tread	Agriflex 372
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	16
Width [mm]	505
Outer diameter [mm]	1465
Static radius [mm]	651
Rolling circumference [mm]	4372
Payload in kg at kph (1)	5150 / 40
Inflation pressure [bar]	3,20
Weight [Kg]	155,99
Tyre content 75% [litre]	355,5
Zulassung	ECE 106
Cyclic field use	CFO
Tyre technology	IF
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential

damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.