



■ ■ ● Bohnenkamp

REIFEN VF 270 / 95 R 54
156 D, TL, AGRIFLEX 363 +
STEEL BELTED, ECE106

Product-No.: 15226897

Technical Information:

Tyre size	VF 270 / 95 R 54
TL / TT	TL
LI / SI	156 D
Tread	Agriflex 363 +
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	10
Permissible rim	9
Width [mm]	287
Outer diameter [mm]	1894
Static radius [mm]	894
Rolling circumference [mm]	5763
Payload in kg at kph (1)	4000 / 65
Inflation pressure [bar]	3,60
Weight [Kg]	101,82
Tyre content 75% [litre]	187,5
Zulassung	ECE 106
Tyre technology	VF
Direction bound	Yes

Hints and features:

- The Alliance 363+ is a VF row crop tyre for heavy, self-propelled field sprayers and tractors
- It offers up to 40% higher load capacity at the same inflation pressure or the same load capacity at up to 40% reduced inflation pressure compared with a standard tyre
- The directional tread pattern design, divided in separate blocks, enables good grip on soft surfaces
- The increased number of lugs and block distribution on the tread pattern ensure good ride comfort and low rolling resistance on roads
- Its large contact area provides high traction, reduced fuel consumption and low soil compaction
- The steel belted casing enables uniform ground pressure distribution and protection against damages, thus ensuring a long service life