



Hints and features:

- The tyre's wide contact area enables good lateral stability when unloading and high flotation on soft surfaces
- The arrangement of the blocks with wide, angled spaces ensures good selfcleaning
- Its special wear-resistant rubber compound was developed for operations on challenging ground such as rocky surfaces, as well as for road use
- High-strength steel belt reinforcements combined with a cut- and crack-resistant rubber compound provide high puncture protection
- The special construction of several steel plies allows high inflation pressures and increases the stability of the tyre
- The asymmetrical arrangement of the blocks, which successively come into contact with the ground surface, reduces the noise generated when driving on the road

REIFEN 560 / 60 R 22.5 165 D, TL, CT HEAVY DUTY, STEEL BELTED

Product-No.: 17415850

## **Technical Information:**

Tyre size	560 / 60 R 22.5
TL/TT	TL
LI/SI	165 D
Tread	СТ
Manufacturer	Nokian
Specification	HD/Steel Belted
Recom. Rim	16.00
Permissible rim	18.00
Width [mm]	560
Outer diameter [mm]	1245
Static radius [mm]	555
Rolling circumference [mm]	3811
Payload in kg at kph (1)	5150 / 65
Inflation pressure [bar]	5,00
Weight [Kg]	138,07
Tyre content 75% [litre]	295
Stud height [mm]	22,0
Zulassung	nicht notwendig

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.